

Triton V2 Dispenser



Main Features

- Excellent industrial design brings pleasant user experience.
- 150-1000V DC wide output voltage range.
- Space-saving for flexible installation method.

Specifications



Product Information	
Input Voltage	480V AC ±10%, 60Hz, L+L+PE
Charging Interface	1 x CCS1 plug or 1 x NACS plug
Output Voltage	150-1000V DC
Output Current	300A rated
Metering	UL meter
User Interface	
Status Indication	LED indicator
Button	Emergency stop button
User Authentication	Free Charging, MAC authentication
Communication	
Connectivity	Ethernet with power cabinet
Communication to the EV	DIN 70121, ISO 15118
Environmental	
Operating Temperature	-22°F to 122°F (-30°C to 50°C)
Storage Temperature	-40°F to 158°F (-40°C to 70°C)
Humidity	5%-95% no condensation
Altitude	≤6561.28' (2000m)
Mechanical	
IP Rating	NEMA 3R
IK Rating	IK10
EVSE Cooling	Forced Air
Charging Cable Length	32.8' (10m)
Dimensions (WxHxD)	1.64' x 1.64' x 0.98' (500 x 500 x 300mm)
Weight	Approx. 70kg (Including charging cable)
Installation	Wall mounting or Gantry mounting
Certification and Standards	
Standards and Compliance	FCC part 15 Class A, UL 2202, UL 2231-1, UL 2231-2, UL 1998, UL991
Certification	FCC, CTEP, OCA2.0.1, NTEP