

Hydrus Liquid-cooled Dispenser



Main Features

- Smart ID design.
- 150-1000V DC wide output voltage range.
- 800A DC max of output current.
- User friendly Cable Management System for easier operation.

Specifications



Product Information	
Input Voltage	230V AC ±10%, 50/60Hz, Single-phase (L+N+PE)
Charging Interface	2 x CCS2 / CCS2 + GBT (Liquid-cooling)
Output Voltage	150-1000V DC
Output Current	600A rated (800A max.)
Metering	CE meter / MID meter / PTB meter
User Interface	
Screen Type	7-inch touch screen
Status Indication	LED indicator
Button	Emergency stop button
User Authentication	RFID card, QR code, APP (optional), Free charging, MAC authentication, Credit card (optional, payment terminal is necessary)
Communication	
Connectivity	Ethernet
Communication to the EV	DIN 70121, ISO 15118
Environmental	
Operating Temperature	-30°C ~ +50°C
Storage Temperature	-40°C ~ +70°C
Humidity	5% ~ 95% no condensation
Altitude	≤2000m
Mechanical	
IP Rating	IP55
IK Rating	IK10 (Screen IK08)
Cooling Method	Liquid Cooling
Charging Cable Length	5m
Dimensions (WxHxD)	500 x 1900 x 450mm (Without CMS)
Weight	198kg (Without CMS)
Installation	Ground mounting
Certification and Standards	
Standards and Compliance	IEC 61851-1, IEC 61851-21-2, IEC 61851-23, LVD 2014/35/EU, RED 2014/53/EU
Certification	CE-RED, CB