

Triton V2 Dispenser



Main Features

- Excellent industrial design brings pleasant user experience.
- 150-1000V DC wide output voltage range.
- 500A DC of output current
- Space-saving for flexible installation method.

Specifications



Product Information	
Input Voltage	230V AC ±10%, 50/60Hz, Single-phase (L+N+PE)
Charging Interface	1 x CCS2 plug
Output Voltage	150-1000V DC
Output Current	380A rated (500A max)
Metering	CE meter / MID meter
User Interface	
Status Indication	LED indicator
Button	Emergency stop button
User Authentication	Free Charging, MAC authentication
Communication	
Connectivity	Ethernet with power cabinet
Communication to the EV	DIN 70121, ISO 15118
Environmental	
Operating Temperature	-30°C ~ +50°C
Storage Temperature	-40°C ~ +70°C
Humidity	5% ~ 95% no condensation
Altitude	≤2000m
Mechanical	
IP Rating	IP55
IK Rating	IK10
EVSE Cooling	Forced Air
Charging Cable Length	10m
Dimensions (WxHxD)	500 x 500 x 300mm
Weight	Approx. 70kg (Including charging cable)
Installation	Wall mounting or Gantry mounting
Certification and Standards	
Standards and Compliance	IEC 61851-1, IEC 61851-21-2, IEC 61851-23, LVD 2014/35/EU, RED 2014/53/EU
Certification	CE-RED, CB