

# Telesto



## Efficiency

Dual connectors,  
simultaneous charging.



## Safety & Protection

Multiple electrical protections  
and a remarkable protection  
level up to IP55 & IK10.



## Smart O&M

Remote monitoring and  
diagnosis, firmware OTA  
upgrading (OCPP1.6J).



# Telesto

Power Input	Input Rating	400Vac±10%, 50/60Hz, three-phase
	Number of Phase/Wire	L1+L2+L3+N+PE
	Internal RCD	Type A 30mA AC + 6mA DC
Power Output	Output Power	2 x 22kW max.
	Charging Interface	IEC 62196-2 Type 2 socket (Case B)
	Output Current	2 x 32A max.
User Interface & Control	Status Indicators	LED strip
	Card Reader	ISO/IEC 14443 A/B, ISO/IEC 18092, IEC/ISO 15693
Communication	Network Interface	4G, Wi-Fi, Ethernet, Bluetooth
	Protocol	OCPP1.6j
Environmental	Operating Temperature	-30°C to 55°C
	Storage Temperature	-40°C to 85°C
	Humidity	5%-95% no condensation
	Altitude	≤2000m above sea level
Mechanical	Ingress Protection	IP55
	Enclosure Protection	1K10
	Cooling	Natural cooling
	Dimension (WxHxD)	472.5*262*1418mm
	Weight	<25kg
	Installation	Ground mounting
Regulation	Certificate	CE,UKCA